



FIREPROOF DOOR “NINZ UNIVER EI₂ 30/60”



Reliable and finest quality fireproof door “Ninz Univer EI₂ 30/60” are used in many countries across the world in public buildings, where safety is at a premium: schools, shopping malls, hospitals, convention centers, hotels, museums and other.

Fireproof doors are made of hot-galvanized sheet metal, painted with epoxy-polyester thermoset powders. Door leaf is heat insulated with treated mineral wool, thus ensuring safety of fire and smoke. Doors are of practical use and easy installed. According to your needs, you can choose single or double leaf doors, with fire resistance of 30 or 60 minutes. Available dimensions - any.

Fireproof door parameters and advantages

■ 50 and 60 mm thickness door leaf is produced of Sendzimir" processed hot-galvanized sheet metal with anti-corrosion protection. Door is heat-insulated with treated mineral wool and fully galvanized, including the "hidden" parts. Optimal corrosion resistance demonstrated by 500 hour salt-fog test.

■ Door is painted with epoxy-polyester thermoset powders in a 180 degrees (Celsius) oven, with substantial paint layer (70 microns plus). Standard door colour – RAL9002, but door can also be ordered in your favorite color from RAL palette or customized with digital design picture (NDD).

■ Door is supplied with assembled 4 – piece corner frame with trim on 4 sides and with anchors for mortar fixing, 2 especially durable (200.000 cycles) hinges with self-closing spring, CE marked as per EN 1935, also lock for fire-rated doors, CE marked according to EN 12209 with cylinder hole and black safety handle with steel core.

■ Fireproof door leaf weight – 34-36 kg/m². Various accessories available (windows, hydraulic door closers, ventilation grill, sealing, stainless steel and anti-panic handles, automatic locks and etc.). Frame plate thickness - 1,5 mm, leaf plate thickness - 0,8 mm.

■ Fireproof door NINZ are CE marked, also compatible with standards UNI 9723 and 1634-1.



Hinge with self-closing spring



Fireproof handle



Fireproof windows



Detachable threshold

Maintenance and guarantee

Guarantee for fireproof door – 24 months.


You can order the door with graphic images on door leaf **□□□** (NINZ DIGITAL DECOR)

According to your needs, you can choose single or double leaf door, opening radius - 180°.




Standard door colour - RAL9002 but you can also choose from standard colours with no price supplement.

RAL 1013	RAL 1015	RAL 5010	RAL 5024	RAL 6000	RAL 7016	RAL 7024	RAL 7035
RAL 7038	RAL 8011	RAL 9001	RAL 9002	RAL 9010	RAL 9011	RAL 9016	RAL 9018



Single leaf reversible door



Double leaf reversible door

