



MULTIPURPOSE OUTSIDE DOOR “NINZ UNIVER” ■■

Multipurpose outside door “Ninz Univer” – optimal choice for private houses, apartments, commercial, industrial and public buildings. The main features of these doors are stable construction, great design and durability.

Door leaf is made of hot-galvanized sheet metal, painted with epoxy-polyester thermoset powders, insulated with treated mineral wool, anti-scratch orange-skin surface. Doors are fully reversible, either single or double leaf, standard and non-standard dimensions.

Door parameters and features

■ 50 mm thickness door leaf is produced of Sendzimir® processed hot-galvanized sheet metal with anti-corrosion protection. Door is heat-insulated with treated mineral wool and fully galvanized, including the “hidden” parts. Optimal corrosion resistance demonstrated by 500 hour salt-fog test.

■ Door surface is painted with epoxy-polyester thermoset powders in a 180 degrees (Celsius) oven, with substantial paint layer (70 microns plus). Standard door colour – RAL9002, but door can also be ordered in your favorite color from RAL palette or customized with digital design picture (NDD).

■ Door is supplied with assembled 4 – piece corner frame with trim on 4 sides and with anchors for mortar fixing, 2 especially durable (200.000 cycles) hinges with self-closing spring, CE marked as per EN 1935, reversible locking mechanism with cylinder hole and black nylon handle.


■ Single leaf door weight – 23 kg/m², double leaf – 22 kg/m². Various accessories available (windows, hydraulic door closers, ventilation grill, sealing, stainless steel and anti-panic handles, automatic locks and etc.). Frame plate thickness - 1,5 mm, leaf plate thickness - 0,8 mm.



Durable hinges



Nylon handle




Windows



Door frame fixing

Maintenance and guarantee

Guarantee for multipurpose outside door – 24 months.


You can order the door with graphic images on door leaf  (NINZ DIGITAL DECOR)

According to your needs, you can choose single or double leaf door, opening radius - 180°.




Standard door colour - RAL9002 but you can also choose from standard colours with no price supplement.

RAL 1013	RAL 1015	RAL 5010	RAL 5024	RAL 6000	RAL 7016	RAL 7024	RAL 7035
RAL 7038	RAL 8011	RAL 9001	RAL 9002	RAL 9010	RAL 9011	RAL 9016	RAL 9018



Single leaf reversible door



Double leaf reversible door

