



Flexible, curtain fire doors MARC-Ok are designed for separating fire zones in different types of industrial premises.

The curtain door is great for underground parkings and shopping malls, where every inch of usable area counts and minimum dimensions are of value.


The curtain material is wound on a shaft and held open with a fuse lock or an electric drive brake. In the event of a fire hazard, the lock/brake opens, the curtain unfolds and locks off the zone.



WORTH TO CHOOSE WHEN:







You need a "clean" design

MARC-OK fire gates are a good choice when the projected spaces must remain unoccupied. These gates do not take up much space and are noticeable.

2

Free space needs to be saved

MARC-OK the gate is mounted above the opening, leaving free walls that can be used for other solutions, and more free parking spaces in the underground car parks.

be protected

Wide areas need to

MARC-OK gates can be up to 16 000 mm wide. They do not require additional columns for installation, making the design process easier and freer.





SPECIFICATION

MAXIMUM DIMENSIONS	16 000 x 10 000 mm
THICKNESS AND WEIGHT	9mm - 6kg/m² (El60); 18mm - 9kg/m² (El120)
FILLING	Patented multilayer fiberglass fabric reinforced with steel wire
COMPONENTS	Made of galvanized steel, the covers can be painted in the chosen RAL color
SIDEROOM	120 mm
HEADROOM	300 - 600 mm (depending on the height of the door)
WORKING TEMPERATURE	-20°C +40°C
MAXIMUM HUMIDITY LEVEL	80%
WARRANTY	2 years
NOTE	The gate is not intended for daily use, but is clo- sed only in the event of a fire or maintenance. The 230 VAC motor requires an uninterruptible power supply.
	"MARC-OK" CURTAIN EXTERNAL MATERIAL



CONTACT US

If you have any questions or would like to purchase fire-protection curtain doors "MARC-OK"? We will be happy to answer all your questions.



IDOMUS UAB

V.Krėvės av. 129, LT-50312, Kaunas Lithuania info@idomus.lt +370 37 308900

idomus.lt