




SECTIONAL DOOR „PRO“





European-standard complying sectional garage doors IDO - PRO - the optimal solution for industrial and commercial buildings. High-quality selection of materials, high technical requirements for this product gives solidity and durability. Industrial sectional door construction and completing parts are redesigned for long-term operation even in intensive use.

- Standard headroom - 420 mm
- Suitable for long-term operation
- Complies with standard EN 13241-1
- 25.000 - 50.000 working cycles
- 5 different lift types
- Panel - Basic (Italy)
- Warranty - 2 years



CONSTRUCTION



40 MM

BASIC (ITALY) - closed contour panel made out of two steel supports, has a geometry to avoid the crush during the closing of the door, accordance with UNI EN 10326 and fill with high-density (40 +/- 4 kg/m³) polyurethane foam.

180 - 420 MM

HEADROOM - standard headroom. Sectional door IDO - PRO lift system depends on door dimensions and headroom height. There are 5 lift types for industrial sectional door IDO - PRO.

25.000

WORKING CYCLES - sectional door IDO - PRO make up with torsion springs. Spring longevity 25 000 - 50 000 opening - closing cycles, diameter 95 - 152 mm. All IDO - PRO sectional door make up with protection against spring break.

2 MM

THICK TRACKS of sheet metal witch are joined using the cold riveting method. During the manufacturing process we do not use welding, so the details of a protective galvanization remains intact.

SPECIFICATIONS

Door type	Industrial
Maximum dimensions	7000 x 7050 mm
Panel thickness, mm	40 mm
Thermal insulation, W/m ² K	0,58 W/m ² K
Air permeability	3 class
Resistance to wind load	2 class
Resistance to water penetration	3 class
Sideroom	≥ 100 mm
Min. Headroom	≥ 180 mm
Spring type	„Torsion“
Spring place	Back/Front
Spring longevity	min. 25 000 cycles
Spring failure safety devices included	Yes
Warranty	2 years

COLORS



You can choose any colour from RAL color palette. We use fine quality German industrial bi-component polyurethane paint to ensure long colour lasting and low fading rate.