



SWINGING SECTIONAL DOOR „SD“



Swinging sectional door IDO-SD - the optimal solution for your home and industrial buildings, when the structure of the building is not designed for lift system. These sectional door we produce exactly according to your individual measurements and personal needs. By creating this garage door model we carefully choose and tested all components, so IDO - SD will serve you long and reliably.

- Single leaf or double leaf
- Produced according to your measurements
- With or without standard 40 mm threshold
- aluminum hinges over the entire height of the door
- Durable and reliable
- Italian panels Basic
- Warranty - 2 years



CONSTRUCTION



40 MM

BASIC (ITALY) - closed contour panel made out of two steel supports, has a geometry to avoid the crush during the closing of the door, accordance with UNI EN 10326 and fill with high-density (40 +/- 4 kg/m³) polyurethane foam.

88 X 44 MM

PROFILED DOORFRAME - it can be equipped with opening garage door IDO-SD. Profiled doorframe is recommended for buildings with higher tightness requirements.

40 X 40 MM

STEEL FRAME - supplied with opening garage door IDO-SD. Sectional door with this frame recommended for buildings, which do not have high tightness requirements.

WINDOWS

FOR NATURAL LIGHTING. According to customer needs, in sectional door can be installed oval or rectangular windows made of impact-resistant polycarbonate.

SPECIFICATIONS

Door type	Residential/Industrial
Max. dimensions	4000 x 4000 mm
Panel thickness	40 mm
Panel thermal insulation	0,58 W/m ² K
Air permeability	3 class
Resistance to wind load	5 class
Resistance to water penetration	3 class
Warianty	2 class

You can choose any colour from RAL color palette. We use fine quality German industrial bi-component polyurethane paint to ensure long colour lasting and low fading rate.

COLORS

YOU CAN choose standard color for swinging sectional door IDO - SD. Also you can choose any colour from RAL color palette.

