

INKEMA SISTEMAS S.L.  
TEL +34 93 544 47 08  
FAX +34 93 572 30 11  
C/ Galileo 2, naves 7 y 8  
08150 Parés del Vallés  
(Barcelona) España



## CONFORMITY DECLARATION

Company : INKEMA SISTEMAS S.L.  
C/Galileo 2, naves 7 y 8  
08150 Parets del Vallés (Barcelona – España)

Declares under its own responsibility that the dock shelters:

Brand : INKEMA  
Model : ABRE (dimensions)  
Fabrication year : 2012  
Serial n° :  
Order ref. :

Have been produced with cold laminated galvanized steel profiles, based on the raw material of strips melted by immersion DX51D + A140 MAC and produced and cut by cold saw according to: DIN EN 10346 and DIN EN 10143, WN 1.0226.

In the same way the protection canvas has been manufactured of semi-rigid PVC canvas and reinforced with internal polyester tissue and produced according to:

Internal tissue	DIN ISO 2076	2 x polyester
Thread quality	DIN EN ISO 2060	2 x 1100/1100 dtex
Thread quantity	DIN EN 1049-2	2 x 12 / 12
Thread density	DIN EN 12127	2 x 265 g/m <sup>2</sup> (approx.)
Coating Material		PVC
Density of set	DIN EN ISO 2286-2	3700 g/m <sup>2</sup> (approx.)
Limit resistance	DIN EN ISO 1421	7800 / 5600 N/5cm
Tear resistance	DIN 53363	800 / 750 N
Adhesion due to welding	IVK 3.13	100 N/5cm
Cold resistance	DIN EN 1876-1	-30°C / -22°F
Flame resistance	DIN 72500	100 mm/min (max.)
Thickness	DIN EN ISO 2286-3	3 mm. (approx.)

Name and surname  
Technical responsible

Place and date